



VISUAL MAGNETICS GRAPHIC SYSTEM®

MagnaMedia® VENEERS

VM-Walnut™ 12

Visual Magnetix® VM-Walnut 12 is a new addition to the Veneer Collection of MagnaMedia®. This woodgrain finish product starts with an 100% FSC certified cellulose base that is dye sublimation printed with a walnut wood grain pattern then encapsulated in a durable resin finish. VM-Walnut 12 is ideal for producing high resolution photo and artwork reproductions, wall murals and POP signage using most digital and analog printing technologies and features a patented Micro-Iron® back-coating enabling displays to be effortlessly updated, installed, layered, transported, stored or recycled.

Features and Benefits

- FSC certified cellulose base. Made from sustainable forestry practices.
- Dye sublimation printed wood grain pattern. Durable print process. Wood "Grain Long" in roll.
- Base is resin encapsulated. Adds semi-matte like finish, durability and anti-microbial properties.
- Easily die cut for interesting overlay accents.
- Water / smudge resistant print surface. Easy to clean.
- 100% opaque, no show through.
- Easy to install: no frames, wraps or stretching necessary.
- Conforms easily to curves and bends for contour applications.

Physical Data

Total Caliper*	12-mil / 305 Micron
Gloss 60°	Semi-matte
Opacity	100%
Fire Rating	Class A (ASTME-84-98)
Optimal Conditions	50% RH / 70°F

Available Sizes

48 in x 100 ft roll – 3in Core

Product Code

VMWLNT-48100

Application Information

- Excellent for architectural woodworking and building applications as well as design, healthcare, hospitality, retail, education, and visual merchandising markets.
- Apply, remove and store like any other MagnaMedia.
- May be overlaid with up to 2 MagnaMedia films.

Printer Compatibility

VM-Walnut12 is compatible UV Cured, HP Latex, and analog printing technologies (see chart).

●	●	●	●	○	×	●	●	×
SCREEN	LITHO / OFFSET	FLEXO	THERMAL / TONER BASED	HP LATEX	SOLVENT (ECO)	UV-CURED	DIGITAL / OFFSET	WATERBASED INK-JET

Recyclability

All MagnaMedia, including VM-Walnut12, will be recycled into energy and new steel production when returned to Visual Magnetix per our "Recycling Retired Graphics" program available for download at www.visualmagnetix.com.

Protecting Images

Liquid laminates are recommended as they can be easily applied to the textured surface with good results. Apply minimally to maintain surface texture. Always pretest liquid laminates for compatibility prior to applying to finished graphic.

Roll-Out



* Thickness and whiteness listed are nominal values.

COMPATIBILITY KEY

- VM certified best results
- Uncertified – Profile dependent
- Will print – Not recommended
- ×

Renew



Visual Magnetix Limited Partnership
1 Emerson Street, Mendon, MA 01756
P 508 381-2400 F 508 381-2401
Toll Free 855 VISMAG4 (855 847-6244)

VisualMagnetix.com
info@visualmagnetix.com